

WorldSID 50th ATD Certification Update

Publication Date: October, 2013



The ISO WorldSID Task Group has recently reviewed certification test corridors for the WorldSID 50th ATD during their regular session meetings in 2012 and 2013 and have updated their recommendations.

Summary

The ISO WorldSID Task Group has completed a review of all the current certification corridors of the WorldSID 50th ATD. The Task Group agreed that the changes in certification outlined in this bulletin are necessary improvements to the test parameters. All certification changes take effect immediately in all new production and re-certifications.

All newly manufactured WorldSID 50th ATDs will be certified to the updated corridors as outlined by the ISO WorldSID Task Group.* Older components due for re-certification will be tested to the new criteria and corridors.

Humanetics will make any future adjustments in WorldSID certification requirements should new recommendations by the Task Group become available.

Corridor and Test Updates

The Task Group first updated corridors for the head drop and pelvis impact in August of 2012. The shoulder, abdomen and thorax were later reviewed resulting in the elimination of the Thorax Impact with Arm test in September of 2013. The table below lists these most recent changes.

WorldSID 50th ATD Certification Updates			
	Specification	Old	New
Head (W50-14014)	Frontal Drop	225-275 g's	205 – 255 g's
	Lateral Drop	99-121 g's	104 – 123 g's
Thorax Impact with Arm	<i>Remove Test from Certification Requirements</i>		
Pelvis (W50-42019)	Probe Force	6.4 – 7.8 kN	6.8 – 8.2 kN
	Lateral Pelvis Acceleration	41 – 51 g's	37 – 47 g's

*Please see accompanying page, *Technical Specifications*, for a complete up-to-date list of WorldSID 50th ATD certification test corridors.

For further inquiries please contact Humanetics Customer Service or your account manager.

Technical Specifications

Certification Test Corridors for the WorldSID 50th ATD

Head Drop - Frontal		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Resultant Acceleration (G)		205 - 255
Peak Lateral Acceleration (G)		< 15
Unimode (%)		< 10

Neck Pendulum Test - Lateral		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Pendulum Velocity (m/s)		3.4 ± 0.1
Pendulum Velocity change (m/s)		
	4 m/s	0.77 - 1.04
	8 m/s	1.60 - 1.90
	12 m/s	2.43 - 3.29
Maximum Angular Displacement Of The Head-form Relative To The Pendulum, Beta (Degrees)		50-61
Decay Time Of Beta To 0 Degree (ms)		58 - 72
Peak Moment At Occipital Condyle (Nm)		55 - 68
Peak Moment Decay Time To 0 Nm (ms)		71 - 87
Peak Forward Potentiometer Angular Displacement (Degrees)		32 - 39
Time Of Peak Forward Potentiometer Angular Displacement (ms)		56 - 68
Peak Rearward Potentiometer Angular Displacement, Theta_f (Degrees)		30 - 37
Time Of Peak Rearward Potentiometer Angular Displacement, Theta_r (ms)		56 - 68
Note: T=0 S At Initial Pendulum Contact With The Honeycomb.		

Shoulder		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Velocity (m/s)		4.3 ± 0.1
Peak Pendulum Force (KN)		2.60 - 3.30
Peak Shoulder Rib Deflection (mm)		35 - 45

Thorax Without Arm		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Velocity (m/s)		4.3 ± 0.1
Peak Pendulum Force (KN)		3.2 - 3.8
Peak Thorax Rib 1 Deflection (mm)		33 - 43
Peak Thorax Rib 2 Deflection (mm)		35 - 43
Peak Thorax Rib 3 Deflection (mm)		32 - 40
Peak T4 Acceleration Along Y Axis (G)		14 - 20
Peak T12 Acceleration Along Y Axis (G)		14 - 22

Head Drop - Lateral		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Resultant Acceleration (G)		104 - 123
Peak Lateral Acceleration (G)		< 15
Unimode (%)		< 10

Abdomen		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Velocity (m/s)		4.3 ± 0.1
Peak Pendulum Force (KN)		2.7 - 3.1
Peak Abdomen Rib 1 Deflection (mm)		33 - 40
Peak Abdomen Rib 2 Deflection (mm)		30 - 36
Peak T12 Acceleration Along Y Axis (G)		15 - 20

Pelvis		ISO 15830
Temperature (°C)		20.6 - 22.2
Humidity (%)		10 - 70
Velocity (m/s)		6.7 ± 0.1
Peak Pendulum Force (KN)		6.8 - 8.2
Peak Pelvis Acceleration (G)		37 - 47
Peak T12 Acceleration Along Y Axis (G)		10 - 14

Filter Class		ISO 15830
Head Drop Test Acceleration Ax, Ay, Az		CFC 1000
Neck Pendulum Test Pendulum Acceleration Angular Displacement Theta F Theta R Theta H Moment Mx Force Fy		CFC 60 CFC 1000 CFC 1000 CFC 1000 CFC 600 CFC 1000
Shoulder Test Pendulum Acceleration Shoulder Rib Deflection		CFC 180 CFC 600
Thorax Without Arm Pendulum Acceleration Thorax Rib 1, 2 And 3 Deflection T4 Acceleration T12 Acceleration		CFC 180 CFC 600 CFC 180 CFC 180
Abdomen Test Pendulum Acceleration Abdomen Rib 1 And 2 Deflection T12 Acceleration		CFC 180 CFC 600 CFC 180
Pelvis Test Pendulum Acceleration Pelvis Acceleration T12 Acceleration		CFC 180 CFC 180 CFC 180

Rev 1, Oct. 2013