

### Deutsche Akkreditierungsstelle

# Annex to the Accreditation Certificate D-K-18446-01-01 according to DIN EN ISO/IEC 17025:2018

**Valid from: 22.10.2025**Date of issue: 22.10.2025

This annex is part of the Accreditation Certificate D-K-18446-01-00.

Holder of the Accreditation Certificate:

Humanetics Europe GmbH Im Breitspiel 6 A, 69126 Heidelberg

with the locations

Humanetics Europe GmbH Airport Boulevard B210, 77836 Rheinmünster

Humanetics Europe GmbH Knorrstraße 147, EG-351, 80788 München

The calibration laboratory meets the requirements of DIN EN ISO/IEC 17025:2018 to carry out the conformity assessment activities listed in this annex. The calibration laboratory meets additional legal and normative requirements, if applicable, including those in relevant sectoral schemes, provided that these are explicitly confirmed below.

The management system requirements of DIN EN ISO/IEC 17025 are written in the language relevant to the operations of calibration laboratories and they conform to the principles of DIN EN ISO 9001.

This annex to the certificate was issued by the Deutsche Akkreditierungsstelle GmbH (DAkkS) and is digitally sealed. This annex to the certificate is only valid together with the written accreditation certificate and reflects the status as indicated by the date of issue. The current status of any valid and surveyed accreditation can be found in the directory of accredited bodies maintained by Deutsche Akkreditierungsstelle GmbH (www.dakks.de).

Abbreviations used: see last page



Calibration in the fields:

### Mechanical quantities

- Force
- Acceleration
- Pressure

### Thermodynamic quantities

### **Temperature quantities**

- Resistance thermometers
- Direct reading thermometers
- Temperature transmitters, data loggers

### **Humidity quantities**

- Devices for relative humidity

Within the measurands/calibration items marked with \*, the calibration laboratory is permitted, without being required to inform and obtain prior approval from DAkkS, to use calibration standards or equivalent calibration procedures listed here with different issue dates. The calibration laboratory maintains a current list of all calibration standards / equivalent calibration procedures within the flexible scope of accreditation.



### Permanent laboratory, Rheinmünster location

### Calibration and Measurement Capabilities (CMC)

Measurement quantity / Calibration item	Range			Measurement conditions / procedure	Expanded uncertainty of measurement	Remarks
Force* Force sensors (safety-belt)	500 N	to	25 kN	ISO/TS 17242:2014-05	1.10-2	Traction force reference standard measuring device with reference transducer Analogue and digital sensors
Force sensors	0,5 kN	to	25 kN	DKD-R 3-3:2018	5·10 <sup>-3</sup>	Compressive force
Multi-component force and moment  Multi-component transducer (ATD)	0.1 kN	to	< 0.5 kN	KW-F05000:2024	1.10-2	reference standard measuring device
	0.5 kN	to	600 kN		5·10 <sup>-3</sup>	with reference transducer
	2 N·m	to	12000 N·m		5·10 <sup>-3</sup>	Analogue and digital sensors
Angular velocity Angular velocity sensors	150°/s	to	3500°/s	KW-AV0002:2021	0.5 %	Rotational via incremental encoder for left and right rotation Analogue and digital sensors
secondary, dynamic	8°/s	to	5000°/s	KW-AV0005:2021 1 Hz to 200 Hz	1.5 % / 1.5°	Analogue and digital sensors Calibration result: complex transfer coefficient (analogue: amplitude/phase, digital: amplitude) and indication deviation



### Permanent laboratory, Rheinmünster location

## Calibration and Measurement Capabilities (CMC)

Measurement quantity / Calibration item	Range			Measurement conditions / procedure	Expanded uncertainty of measurement	Remarks
Acceleration * Acceleration sensors	200 m/s <sup>2</sup>	to	20000 m/s <sup>2</sup>	Shock excitation DKD-R 3-1 page 2:2018	1.2 %	Analogue and digital sensors
	5 m/s²	to	200 m/s²	Sinusoidal excitation DKD-R 3-1 page 3:2018  10 Hz to 5 kHz > 5 kHz to 10 kHz	1.2 % / 1.0 ° 2.5 % / 1.5 °	Analogue and digital sensors Calibration result: complex transfer coefficient (analogue: amplitude/phase, digital: amplitude) and indication deviation
Pressure* Positve pressure	0 bar	to	6 bar	DKD-R 6-1:2014	1 %	
Absolute pressure	1 bar	to	7 bar	DKD-R 6-1:2014	1 %	
Temperature*  Resistance thermometers, direct reading thermometers, temperature transmitters and data loggers with resistance sensor	10 °C	to	50 °C	DKD-R 5-1:2018 in temperature / humidity generator	0.15 K	Comparison with display of the temperature / humidity generator
Temperature indicators and simulators for base metal thermocouples	−50 °C	to	500 °C	DKD-R 5-5:2018	0.2 K	Characteristic curve according to DIN EN 60584:2014
Relative humidity* Direct reading electric hygrometers, data loggers	10 %	to	80 %	DKD-R 5-8:2019 in temperature / humidity generator Measurement in air Air temperature: 20 °C to 25 °C	3 %	Comparison with display of the temperature / humidity generator Measurement uncertainty expressed as absolute value of the relative humidity



### Permanent laboratory, München location

### Calibration and Measurement Capabilities (CMC)

Measurement quantity / Calibration item		Rang	e	Measurement conditions / procedure	Expanded uncertainty of measurement	Remarks
Acceleration*  Acceleration sensors, accelerometer measurement chains	200 m/s <sup>2</sup>	to	2000 m/s <sup>2</sup>	Shock excitation DKD-R 3-1 page 2: 2018	1.5 %	Analogue and digital sensors
Force* Force sensors	2 kN	to	20 kN	DKD-R 3-3:2018	2·10-3	Analogue and digital sensors
Multi-component force and moment Multi-component transducer (ATD)	0.05 kN	to	< 0.5 kN	KW-F05000:2021	2·10-2	Compressive force reference standard measuring device with reference transducer Analogue and digital sensors
	0.5 kN	to	25 kN		5·10 <sup>-3</sup>	
	3 N·m	to	< 30 N·m		2·10 <sup>-2</sup>	
	30 N·m	to	1200 N·m		5·10 <sup>-3</sup>	

### Abbreviations used:

DIN Deutsches Institut für Normung e.V. – German institute for standardization

EN Europäische Norm – European Standard
 IEC International Electrotechnical Commission
 ISO International Organization for Standardisation
 DKD-R Richtlinie des Deutschen Kalibrierdienstes (DKD),

herausgegeben von der Physikalisch-Technischen Bundesanstalt

KW- calibration procedure of the Humanetics Europe GmbH